



FAST KWARC

acrylic structural paint "Quartz coat" type

- APPLICATION** **FAST KWARC** is an acrylic structural paint meant for creating decorative layers on cement plasters, cement-limestone, thinly-layered mineral and dyspersoid plasters, and on surfaces made of concrete, brick, plaster, plaster-cardboard panels and asbestos-cement boards. The product may be applied both indoors and outdoors.
- CHARACTERISTICS** **FAST KWARC** is a well-covering acrylic structural paint with fine quartz grain, long-lasting and resistant to hits and weather conditions. Easy to apply, it corrects minor unevenness creating a perfectly solid layer. Basic colour-white. The possibility of colouring in wide arrange of FAST Kolor System.
- PREPARATION OF THE BASE** **FAST KWARC** should be laid on strong, clean, dry, solid, grease-free and dust-free surfaces. Visible scratches and defects must be corrected and completed. On absorptive, falling off and dusting surfaces **FAST GRUNT G** must be laid.
- INSTRUCTIONS FOR PREPARATION AND USE** Stir before use carefully. As a primer **FAST GRUNT M** (white or in some other colour) should be used. Not a diluted layer of the mortar lay with the façade brush, mini bench-brush, structural roll or long float. The final design should be shaped with a proper roll or some other tool. **FAST KWARC** should be laid in surface and environment temperature between +5°C and +25°C. Do not lay it in rain, strong wind or in full sun. Time of drying: around 2 hours. Further layers should be laid after at least 4 hours.
- The general technology for wall painting should be kept.
- EFFICIENCY** 0,30-0,60 l/m² per one layer, depending on the thickness of the structure.
- STORAGE** Store and transport in tight closed packaging, in temperature between +5°C and +25°C. Utility period is 12 months.
- TECHNICAL SPECIFICATIONS**
- | | |
|-------------------|-------------------------------|
| Base temperature: | between +5°C and +25°C |
| Adherence | min. 0,30 MPa |
| Open time: | appr. 20 min |
- PACKAGES** Plastic buckets of 4l and 10 l.
Pallets of 512 kg in 4 l plastic buckets (80 items).
Pallets of 704 kg in 10 l plastic buckets (44 items).
- STANDARDS / NORMS** Manufactured according to: PN-C-81913:1998
Sanitary Certificate issued by the State Sanitary Department no HK/B/0073/01/2004.
- NOTE** Fresh cement-lime plasters and fresh reinforced coats made according to insulation systems must be at least 6 weeks. Tools to be cleaned with water.
- The range of the product use recommended and defined in these instructions does not relieve the user/contractor from the obligation of carrying out works following both building principles as well as labour safety regulations.
P.W. FAST guarantees and shall be liable for the product quality, however it cannot control methods in which the product was used and under what conditions.